

## MONOBLOCKS AND REFRIGERATED SYSTEMS COMMERCIAL SPLIT UNITS

### Commercial Split Units

- Electronic control panel
- Expansion by means of thermal expansion valve
- Cable for door heater (on low temperature units)
- Fixed calibration low pressure switch
- High pressure switch on all three-phase units and on single-phase HMM122-152 (in compliance with the "pressure equipment" directive 97/23/CE)
- Direct drainage of condensate water with heater
- Hermetic compressor
- Electric defrost
- Filter on the liquid line
- Remote control panel connected to the unit with a 5m long cable
- Sight glass
- All units are equipped with a liquid receiver complying (in compliance with the "pressure equipment" directive 97/23/CE)
- Pre-arrangement for door switch and room light connections



## TN +5°C/-5°C

### DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

### HMM152

<b>Unità</b> <b>Unit</b> <b>Unit</b>	Tensione   Voltage   Voltage	volt/f/Hz	230/1/50
	Assorbimento   Absorption   Absorption	W	1923
	Compressore   Compressor   Kompressor	m <sup>3</sup> /h	5,69
	Tipo comp.   Comp. Type   Comp. Type	E/S	E
	Sbrinamento   Defrost   Defrost	El / Gc	1400
	Refrigerante   Coolant   Coolant		R452A
<b>Condensatore</b> <b>Condensator</b> <b>Condensator</b>	Ventole   Fans   Fans	n°x Ø	1X350
	Portata aria   Air flow   Air flow	m <sup>3</sup> /h	2200
<b>Evaporatore</b> <b>Evaporator</b> <b>Evaporator</b>	Ventole   Fans   Fans	n°x Ø	3X254
	Portata aria   Air flow   Air flow	m <sup>3</sup> /h	2350
	Gittata   Air-throw   Air-throw	m	m.6
<b>Dimensioni</b> <b>Sizes</b> <b>Sizes</b>	Larghezza   Width   Width	mm	930 (C) / 1470 (E)
	Profondità   Depth   Depth	mm	790 (C) / 620 (E)
	Altezza   Height   Height	mm	750 (C) / 390 (E)
	Peso   Weight   Weight	kg	89 (C) / 40 (E)

### TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

			m <sup>3</sup>	W
<b>TA +20°C</b>	<b>TC +5°C</b>		63,5	<b>4472</b>
	<b>TC 0°C</b>		49,4	<b>3763</b>
	<b>TC -5°C</b>		38,1	<b>3121</b>
<b>TA +32°C</b>	<b>TC +5°C</b>		51,9	<b>3655</b>
	<b>TC 0°C</b>		40,6	<b>3182</b>
	<b>TC -5°C</b>		29,5	<b>2558</b>
<b>TA +43°C</b>	<b>TC +5°C</b>		36,7	<b>3101</b>
	<b>TC 0°C</b>		27,4	<b>2566</b>
	<b>TC -5°C</b>		20,3	<b>2082</b>