

MONOBLOCKS AND REFRIGERATED SYSTEMS

COMMERCIAL SPLIT UNITS

Commercial Split Units

Electronic control panel
 Expansion by means of thermal expansion valve
 Cable for door heater (on low temperature units)
 Fixed calibration low pressure switch
 High pressure switch on all three-phase units and on single-phase HMM122-152
 (in compliance with the "pressure equipment" directive 97/23/CE)
 Direct drainage of condensate water with heater
 Hermetic compressor
 Electric defrost
 Filter on the liquid line
 Remote control panel connected to the unit with a 5m long cable
 Sight glass
 All units are equipped with a liquid receiver complying (in compliance with the
 "pressure equipment" directive 97/23/CE)
 Pre-arrangement for door switch and room light connections



TN +5°C/-5°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

HMM151

Unità Unit Unit	Tensione Voltage Voltage	volt/f/Hz	400/3/50
	Assorbimento Absorption Absorption	W	2060
	Compressore Compressor Kompressor	m³/h	5,69
	Tipo comp. Comp. Type Comp. Type	E/S	E
	Sbrinamento Defrost Defrost	El / Gc	1400
	Refrigerante Coolant Coolant		R452A
Condensatore Condensator Condensator	Ventole Fans Fans	n°x Ø	1X350
	Portata aria Air flow Air flow	m³/h	2200
Evaporatore Evaporator Evaporator	Ventole Fans Fans	n°x Ø	3x254
	Portata aria Air flow Air flow	m³/h	2350
	Gittata Air-throw Air-throw	m	m.6
Dimensioni Sizes Sizes	Larghezza Width Width	mm	930 (C) / 1470 (E)
	Profondità Depth Depth	mm	790 (C) / 620 (E)
	Altezza Height Height	mm	750 (C) / 390 (E)
	Peso Weight Weight	kg	88 (C) / 40 (E)

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

		m³	W
TA +20°C	TC +5°C	63,5	4472
	TC 0°C	49,4	3763
	TC -5°C	38,1	3121
TA +32°C	TC +5°C	51,9	3655
	TC 0°C	40,6	3182
	TC -5°C	29,5	2558
TA +43°C	TC +5°C	36,7	3101
	TC 0°C	27,4	2566
	TC -5°C	20,3	2082