

MONOBLOCKS AND REFRIGERATED SYSTEMS COMMERCIAL SPLIT UNITS

Commercial Split Units

- Electronic control panel
- Expansion by means of thermal expansion valve
- Cable for door heater (on low temperature units)
- Fixed calibration low pressure switch
- High pressure switch on all three-phase units and on single-phase HMM122-152 (in compliance with the "pressure equipment" directive 97/23/CE)
- Direct drainage of condensate water with heater
- Hermetic compressor
- Electric defrost
- Filter on the liquid line
- Remote control panel connected to the unit with a 5m long cable
- Sight glass
- All units are equipped with a liquid receiver complying (in compliance with the "pressure equipment" directive 97/23/CE)
- Pre-arrangement for door switch and room light connections



BT -18°C/-25°C

DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

HML300

| | | | |
|---|--|-------------------|--------------------|
| Unità Unit Unit | Tensione Voltage Voltage | volt/f/Hz | 400/3/50 |
| | Assorbimento Absorption Absorption | W | 2400 |
| | Compressore Compressor Kompressor | m ³ /h | 12,92 |
| | Tipo comp. Comp. Type Comp. Type | E/S | E |
| | Sbrinamento Defrost Defrost | El / Gc | 1400 |
| | Refrigerante Coolant Coolant | | R452A |
| Condensatore Condensator Condensator | Ventole Fans Fans | n°x Ø | 1X350 |
| | Portata aria Air flow Air flow | m ³ /h | 2200 |
| Evaporatore Evaporator Evaporator | Ventole Fans Fans | n°x Ø | 3X254 |
| | Portata aria Air flow Air flow | m ³ /h | 2350 |
| | Gittata Air-throw Air-throw | m | m.6 |
| Dimensioni Sizes Sizes | Larghezza Width Width | mm | 930 (C) / 1470 (E) |
| | Profondità Depth Depth | mm | 790 (C) / 620 (E) |
| | Altezza Height Height | mm | 750 (C) / 390 (E) |
| | Peso Weight Weight | kg | 100 (C) / 40 (E) |

TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

| | | | m ³ | W |
|-----------------|-----------------|--|----------------|-------------|
| TA +20°C | TC -18°C | | 37,9 | 3046 |
| | TC -22°C | | 29,7 | 2595 |
| | TC -25°C | | 23,7 | 2772 |
| TA +32°C | TC -18°C | | 26 | 2467 |
| | TC -22°C | | 19,4 | 2045 |
| | TC -25°C | | 15,1 | 1762 |
| TA +43°C | TC -18°C | | 21,1 | 2082 |
| | TC -22°C | | 15,1 | 1692 |
| | TC -25°C | | 11,8 | 1442 |