

## MONOBLOCKS AND REFRIGERATED SYSTEMS COMMERCIAL CEILING MOUNTED

### COMMERCIAL CEILING-MOUNTED

- Electronic control panel
- Expansion by means of capillary tube
- Cable for door heater (on low temperature units)
- Cable for cold room light
- Fixed calibration low pressure switch
- High pressure switch on all three-phase units and on single-phase CCM122-152 (in compliance with the "pressure equipment" directive 97/23/CE)
- Direct drainage of condensate water with heater
- Hermetic compressor
- Hot gas defrost
- Filter on the liquid line
- Remote control panel connected to the unit with a 5m long cable
- Prearrangement for door micro switch connection



## BT -18°C/-25°C

### DATI TECNICI | TECHNICAL DATA | TECHNICAL DATA

CML230

<b>Unità</b> <b>Unit</b> <b>Unit</b>	Tensione   Voltage   Voltage	volt/f/Hz	400/3/50
	Assorbimento   Absorption   Absorption	W	2630
	Compressore   Compressor   Kompressor	m <sup>3</sup> /h	11,54
	Tipo comp.   Comp. Type   Comp. Type	E/S	E
	Sbrinamento   Defrost   Defrost	El / Gc	Gc
	Refrigerante   Coolant   Coolant		R452A
<b>Condensatore</b> <b>Condensator</b> <b>Condensator</b>	Ventole   Fans   Fans	n°x Ø	2X254
	Portata aria   Air flow   Air flow	m <sup>3</sup> /h	2100
<b>Evaporatore</b> <b>Evaporator</b> <b>Evaporator</b>	Ventole   Fans   Fans	n°x Ø	2X200
	Portata aria   Air flow   Air flow	m <sup>3</sup> /h	1100
	Gittata   Air-throw   Air-throw	m	m.5
<b>Dimensioni</b> <b>Sizes</b> <b>Sizes</b>	Larghezza   Width   Width	mm	900
	Profondità   Depth   Depth	mm	650
	Altezza   Height   Height	mm	980
	Peso   Weight   Weight	kg	101

### TABELLA DI SELEZIONE | SELECTION TABLE | AUSWAHLTABELLE

			m <sup>3</sup>	W
TA +20°C	TC -18°C		35	2610
	TC -22°C		26,6	2145
	TC -25°C		20,7	1810
TA +32°C	TC -18°C		21,1	1960
	TC -22°C		15,4	1565
	TC -25°C		12,1	1335
TA +43°C	TC -18°C		15,7	1475
	TC -22°C		11,3	1185
	TC -25°C		8,7	1005